GARRETT



BEST IN CLASS SECURITY

Enter *Paragon*. For security supervisors unwilling to compromise on security results. Garrett's *Paragon* walk-through metal detector is a game changer. Powerful performance meets new heights of flexibility and ease-of-use in a fresh, sophisticated package.



Designed to meet certification:-



DHSSafety Act
Certified



ECAC (European airports)



STAC (French airports)



Aena (Spanish airports)



CJIAC (Japanese airports)



DfT (U.K. airports)



AMBISCAN™



IP65



66 ZONES



QUICK-Q®



ZERO TOUCH $^{\text{\tiny TM}}$

Paragon Advantage



Ambiscan™. EXCLUSIVE

Cut checkpoint footprint in half. Directional sensitivity reduces operator fatigue and allows different detection targets on egress versus ingress.



66 Zones. EXCLUSIVE

Granular awareness of alarm area top-tobottom and left/middle/right is unmatched in the world of security metal detection.



Bilateral detection. EXCLUSIVE

Provides evenly distributed detection, simplifies multi-unit setup, and achieves superior target analysis to single-sided detection.



IP65.

Exacting construction provides protection from dust and moisture.



Cellphone discrimination.

Optional settings allow cell phones to be ignored while still catching mass casualty weapons.



Zero Touch™.

NFC card reader allows secure settings adjustment without mechanical insertion, meaning less wear and fewer card replacements.



Integrated UPS.

Includes internally-mounted 1 hour emergency power ensures sustained operation in the event of accidental AC disconnect or power outage.

Paragon Accessories
Paragon Adhesive Floor Mount Kit
Paragon IR Remote Control
Quick-Swap Battery Pack 10Hr
Transportation Brace
Walkthrough Caster Set
iC Module, Wired/Wireless
I/O Relay Module

Sensitivity Zone Indications 66 zones Overhead Control Unit All electronics—LED, alarm light, bar graph, control touch pads—integrated to eliminate exposed wires, tampering. Tamper-Proof Settings Three levels of access control Self Diagnostic Program Complete and automatic Zone Sensitivity Boost 22 Independently adjustable boosts Quick-Swap Battery Packs 1.8 amp-hour battery module provides typical 1 hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play'. Passageway Interior Size Width 30" (0.76 m) Depth 23" (0.58 m) Overall Exterior Size Width 36" (0.91 m) Height 87" (2.21 m) Depth 28" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (2.21 m) Depth 9" (2.20 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +13° F (50° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or of Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CIIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Standard Programs	Over 23 application programs included
Overhead Control Unit All electronics—LED, alarm light, bar graph, control touch pads—integrated to eliminate exposed wires, tampering. Tamper-Proof Settings Three levels of access control Self Diagnostic Program Complete and automatic Zone Sensitivity Boost 22 Independently adjustable boosts Quick-Swap 1.8 amp-hour battery module provides typical 1 hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play'. Passageway Interior Size Width 30" (0.76 m) Height 81.5" (2.07 m) Depth 23" (0.58 m) Overall Exterior Size Width 35" (0.90 m) Height 87" (2.21 m) Depth 22" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (2.2 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +13+1° (55° C) Battery operation: 14° F (-10° C) to +174° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewriting, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CIIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Sensitivity	Up to 200 distinct sensitivity levels
touch pads—integrated to eliminate exposed wires, tampering. Tamper-Proof Settings Three levels of access control Self Diagnostic Program Complete and automatic Zone Sensitivity Boost 22 Independently adjustable boosts Quick-Swap 1.8 amp-hour battery module provides typical 1 hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play'. Passageway Interior Size Width 30" (0.76 m) Height 81.5" (2.07 m) Depth 23" (0.58 m) Overall Exterior Size Width 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (2.2 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Zone Indications	66 zones
Self Diagnostic Program Zone Sensitivity Boost 22 Independently adjustable boosts Quick-Swap Battery Packs 1.8 amp-hour battery module provides typical 1 hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play.' Passageway Interior Size Width 30" (0.76 m) ADA width 32.5" (0.83 m) Height 81.5" (2.07 m) Depth 23" (0.58 m) Overall Exterior Size Width 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (.22 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Overhead Control Unit	touch pads—integrated to eliminate exposed
Zone Sensitivity Boost22 Independently adjustable boostsQuick-Swap1.8 amp-hour battery module provides typical 1 hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play'.Passageway Interior SizeWidth 30" (0.76 m)	Tamper-Proof Settings	Three levels of access control
Quick-Swap1.8 amp-hour battery module provides typical 1 hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play.'Passageway Interior SizeWidth 30" (0.76 m) Height 81.5" (2.07 m) Depth 23" (0.58 m)ADA width 32.5" (0.83 m)Overall Exterior SizeWidth 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m)ADA width 32.5" (0.83 m)Shipping SizeWidth 36" (0.91 m) Height 89" (2.26 m) Depth 9" (.22 m)Shipping / AssembledWeight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg)TemperaturesOperating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C)PowerFully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed.Regulatory InformationMeets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending.WeatherproofingMeets IP 65, IEC 529 Standard for moisture, foreign matter protectionConstructionAttractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Self Diagnostic Program	Complete and automatic
hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed wires, tampering and are 'plug and play'. Passageway Interior Size Width 30" (0.76 m) ADA width 32.5" (0.83 m) Height 81.5" (2.07 m) Depth 23" (0.58 m) Overall Exterior Size Width 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (.22 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Zone Sensitivity Boost	22 Independently adjustable boosts
Height 81.5" (2.07 m) Depth 23" (0.58 m) Overall Exterior Size Width 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (.22 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	·	hour operating time. Optional 14 amp-hour battery module provides up to 10 hours operating time. Both batteries are integrated to eliminate exposed
Height 87" (2.21 m) Depth 23" (0.58 m) Shipping Size Width 36" (0.91 m) Height 89" (2.26 m) Depth 9" (.22 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Passageway Interior Size	Height 81.5" (2.07 m)
Height 89" (2.26 m) Depth 9" (.22 m) Shipping / Assembled Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg) Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Overall Exterior Size	Height 87" (2.21 m)
Temperatures Operating on AC: -4° F (-20° C) to +131° F (55° C) Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Shipping Size	Height 89" (2.26 m)
Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C) Battery storage: -14° F (-10° C) to +176° F (80° C) Power Fully automatic 100 to 240 VAC~± 10%, 50 or 60 Hertz, 60 watts; no rewiring, switching or adjustments needed. Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Shipping / Assembled	Weight 180 lbs. (81.64 kg) / 152 lbs. (68.95 kg)
Regulatory Information Meets Electrical Safety and Compatibility Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Temperatures	Battery operation: 14° F (-10° C) to +140° F (60° C) Humidity to 95% non-condensing Storage: -22° F (-30° C) to 176° F (80° C)
Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC certifications pending. Weatherproofing Meets IP 65, IEC 529 Standard for moisture, foreign matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Power	60 Hertz, 60 watts; no rewiring, switching or
matter protection Construction Attractive scratch and mar-resistant laminate. Detection Head and Support: heavy duty aluminum.	Regulatory Information	Requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE. Design to meet international airport stardards such as STAC, AENA, CJIAC, DFT. ECAC
laminate. Detection Head and Support: heavy duty aluminum.	Weatherproofing	
Random Alarm Feature Adjustable from 0 to 100 percent.	Construction	laminate. Detection Head and Support: heavy
	Random Alarm Feature	Adjustable from 0 to 100 percent.

Part No.	Model/Clearance
1172002	International Standard 30"
1172004	International ADA-compliant 32.5"

Paragon Walk-Through Metal Detector

www.garrettaustralia.com.au



GARRETT AUSTRALIA

Arundel Business Park, 2/8 Distribution Court Arundel, Gold Coast, Queensland 4214 Tel: 07 5551-0344

Email: security@garrettaustralia.com.au